

Jan-17

# INDUSTRIAL PRICE SHEET

**SHIP TO:**

Company Name: \_\_\_\_\_

Address \_\_\_\_\_

City: \_\_\_\_\_ State \_\_\_\_\_ Zip: \_\_\_\_\_

Contact Name/ Ordered By: \_\_\_\_\_

Phone Number : \_\_\_\_\_ Fax Number: \_\_\_\_\_

**BILL TO:**

Company Name : \_\_\_\_\_

Address : \_\_\_\_\_

City: \_\_\_\_\_ State: \_\_\_\_\_ Zip: \_\_\_\_\_

PO# \_\_\_\_\_

MODEL	DESCRIPTION	INDUSTRIAL
DT-3	LightGage™ Detector System. Used for 2 Plane Optical Position Sensing. Includes: DT3 LightGage Sensor Unit, DT3 LightGage Software Suite, Laptop Computer and Power Supply, L100M MX Laser Precision Level, AP1000 Leveling Adapter Plate, AP94 Mounting Bracket with Hardware, AP353A Magnetic Mounting Base, 14' and 3' Ethernet Cables, PoE Portable Battery Supply with Charger and Pelican Hard Shell Carrying Case. Dimension/Weight each case: 22"L x18"W x 10"H / 35 Lbs.	\$7,500.00
109091W	Super LED Strobe, MSHA Approved, with Non-Replaceable Batteries includes 1 case of 12 units	\$2,220.00
1090W	Super LED Strobe, MSHA Approved, with Replaceable Batteries includes 1 case of 12 units	\$2,580.00
1091	Replaceable Battery Pack for Model 1090 LED Strobe System. MSHA Approved. Includes 12 units	\$720.00
108081W	LED Strobe, MSHA Approved, Non-Replaceable Batteries. Super Bright, White LEDs Flash every ten seconds for two years. Magnetic Direction and Location Marker. Includes 12 units per case. Dimension per unit: 4 1/4"L x 3 1/4" W x 2"H.	\$1,200.00
108081RG	LED Strobe, MSHA Approved, Non-Replaceable Batteries. Super Bright, Red/Green LEDs Flash every ten seconds for two years. Magnetic Direction Marker. Includes 12 units per case. Dimension per unit: 4 1/4"L x 3 1/4" W x 2"H.	\$1,200.00
1080W	LED Strobe, MSHA Approved, Replaceable Batteries. Super Bright, White LEDs Flash every ten seconds for two years. Magnetic Direction and Location Marker. Includes Model 1081 Battery Pack and 12 units per case. Dimension per unit: 4 1/4"L x 3 1/4" W x 2"H.	\$1,440.00
1080R/G	LED Strobe, MSHA Approved, Replaceable Batteries. Super Bright, Red/Green LEDs Flash every ten seconds for two years. Magnetic Direction and Location Marker. Includes Model 1081 Battery Pack and 12 units per case. Dimension per unit: 4 1/4"L x 3 1/4" W x 2"H.	\$1,440.00
1081	Replaceable Battery Pack for Model 1080 LED Strobe System. MSHA Approved. Includes 12 units per case.	\$480.00
L350	Standard Alignment Laser (For use in non-gaseous environments). Includes adjustable spad hanging tabs & 5 "AA" size Batteries. Solid Brass. Dimensions 14"L x 1" Dia.	\$957.00
L350 MSHA	Intrinsically Safe Alignment Laser (Mine Safety & Health Admin.) Certified for use in hazardous environments esp. Methane-Air Mixtures. Includes adjustable spad hanging tabs & 5 "AA" size Batteries. Solid Brass. Dimensions 14"L x 1" Dia. Weight 2 1/2 Lbs.	\$1,520.00
GL350	Green Laser Technology™ Alignment Laser (For use in non-gaseous environments). Includes adjustable spad hanging tabs and 2 "D" size Batteries. Solid Brass. Dimension 11 1/4"L x 1 5/8" Dia.	\$1,230.00

Weight 4 Lbs.

<b>MODEL</b>	<b>DESCRIPTION</b>	<b>INDUSTRIAL</b>
GL350 MSHA	Green Laser Technology™ Intrinsicly Safe Alignment Laser (Mine Safety & Health Admin.) Certified for use in hazardous environments esp. Methane-Air Mixtures. Includes adjustable spad hanging tabs & 2 "D" size Batteries. Solid Brass. Dimensions 11 1/4"L x 1 5/8" Dia. Weight 4 Lbs.	\$1,805.00
GL35096 MSHA	Complete Hard Mount Mining and Tunneling Alignment Kit Including: GL350 MSHA Alignment Laser, AP96 Hard Mount which includes: AP97 Mounting Block, 4- AP11 SS Rock Bolts, 2- AP12 Extension Nuts, 4- AP13 Rock Anchors 1 1/4" Dia., 2- AP94 Mounting Brackets, AP65 SS Gimbal Support Bracket, WP59 Fine Beam Steering Optics and AP46 Foam Filled, Hard Case Hard Case.	\$3,200.00
L350X MSHA	Extremely Bright Intrinsicly Safe Alignment Laser (Mine Safety & Health Admin.) Certified for use in hazardous environments esp. methane-air mixtures. Includes: Adjustable spad hanging tabs, 10LD 10mw, 635nm, laser diode and (5) "AA" size batteries. Solid brass. Dimensions: 17"L x 1" dia.	\$1,752.00
L355X	Extreme Long Distance Alignment Laser. Includes: Adjustable spad hanging tabs, 10LD 10mw, 635nm, Circulaser™ laser diode with u lens, AP355 2-mile beam extender and (5) "AA" size batteries. Solid brass. Dimensions: 17"L x 1" dia.	\$1,525.00
L355X MSHA	Extreme Long Distance Intrinsicly Safe Alignment Laser (Mine Safety & Health Admin.) Certified for use in hazardous environments esp. methane-air mixtures. Includes: Adjustable spad hanging tabs, 10LD 10mw, 635nm, Circulaser™ laser diode with u lens, AP355 2-mile beam extender and (5) "AA" size batteries. Solid brass. Dimensions: 17"L x 1" dia.	\$1,990.00
GL350X	Green Laser Technology™ Extreme Long Distance Alignment Laser. Includes: Adj. spad hanging tabs,	\$1,874.00
GL350X MSHA	Green Laser Technology™ Extreme Long Distance Intrinsicly Safe Alignment Laser. MSHA Certified for use in hazardous environments esp. methane-air mixtures. Includes: Adjustable spad hanging tabs, GAP355 2-mile Beam Extender, 80mm fl objective lens and 2 "D" size Batteries. Solid brass. Dimensions: 11 1/4"L x 1 5/8" Dia., Weight 4 Lbs.	\$2,450.00
L700	Dual Beam, 2 eye visible laser beams shoot in opposite directions. Methane-Air Mixtures Includes adjustable spad hanging tabs & 6 "AA" size Batteries Solid Brass. Dimensions 20 "L x 1" Dia.	\$1,360.00
L700 MSHA	Dual Beam, Intrinsicly Safe Alignment Laser (Mine Safety & Health Admin.) 2 eye visible laser beams shoot in opposite directions. Certified for use in hazardous environments esp. Methane-Air Mixtures. Includes adjustable spad hanging tabs & 6 "AA" size Batteries Solid Brass. Dimensions 20 "L x 1" Dia.	\$2,035.00
GL700	Green Laser Technology™ Dual Beam, 2 eye visible, green laser beams shoot in opposite directions. Methane-Air Mixtures. Includes adjustable spad hanging tabs & 4 "AA" size Batteries Solid Brass. Dimensions 20 "L x 1" Dia.	\$1,645.00
GL700 MSHA	Green Laser Technology™ Dual Beam, Intrinsicly Safe Alignment Laser MSHA. 2 eye visible, green laser beams shoot in opposite directions. Certified for use in hazardous environments esp. Methane-Air Mixtures. Includes adjustable spad hanging tabs & 4 "AA" size Batteries Solid Brass. Dimensions 20 "L x 1" Dia.	\$2,320.00
L202	Dual Beam Alignment Laser. 2 eye visible laser beams shoot in opposite directions.	\$895.00

Includes magnetic base, backlit 5 arc minute level vial. Dimensions 9.5"L x 1.625"H x .75"W

L202 MSHA MSHA Certified L202 Dual Beam Alignment. \$1,095.00

<b>MODEL</b>	<b>DESCRIPTION</b>	<b>INDUSTRIAL</b>
GL202	Green Beam Technology™ Dual Beam Alignment Laser. 2 eye visible laser beams shoot in opposite directions. Includes magnetic base, backlit 5 arc minute level vial and built-in spad hanging tabs. Dimensions 9.5"L x 1.625"H x .75"W	\$940.00
GL202 MSHA	Green Beam Technology™ Dual Beam Intrinsically Safe Alignment Laser MSHA. 2 eye visible, green laser beams shoot in opposite directions. Certified for use in hazardous environments especially Methane-Air Mixtures. Includes adjustable spad hanging tabs & 4 "AA" size Batteries. Solid Brass. Dimensions 9.5"L x 1.625"H x .75"W	\$1,575.00
L100M	MX Laser Precision Level™. Includes: 5 arc minute level vial, 12.5 mm optics for long distance, 635 nm, 5 mw laser system and machined bottom for precise layouts.	\$407.00
L100X	Extreme" Laser Precision Level™. Includes: 10mw, 635nm laser, 1) 5 arc minute level vial, (2) 30 arc minute plumb vials, , machined bottom for precision layouts. Uses all standard L100M style accessories. Dimensions 1"H x 1 1/8"W x 9"L.	\$589.00
L100MLK	MX Layout Kit. Includes: L100M laser, AP100A leveling adapter plate, AP90C Beam Bender™ and AP40 hard case.	\$750.00
L100M MSHA	Intrinsically Safe Leveling & Alignment Laser. (Mine Safety & Health Admin.) Certified for use in hazardous environments esp. methane-air mixtures. Includes Level & Plumb vials and machined bottom for precision layouts. Uses all Standard L100 style accessories. Dimensions 1"H x 1 1/8"W x 9"L.	\$920.00
GL100M	Green Laser Technology™ MX Laser Precision Level. Includes: 5 arc minute level vial, 50mm fl optics for long distance, 523 nm, 5 mw laser system and machined bottom for precise layouts.	\$710.00
GL100M MSHA	Green Laser Technology™ Intrinsically Safe Leveling & Alignment Laser. MSHA Certified for use in hazardous environments esp. methane-air mixtures. Includes Level & Plumb vials and machined bottom for precision layouts. Uses all Standard L100 style accessories. Dimensions 1"H x 1 1/8"W x 9"L.	\$1,520.00
L50XP	Extreme Performance Laser Micro Level™. 10mW Laser Diode (40 times brighter) Includes: Torpedo shape and three angle vials. Dimensions: 6 1/2"L x 1 3/8" H x 5/8" W	\$295.00
GL50XP	Green Laser Technology™ Extreme Performance Laser Micro Level. 10 times brighter than red Includes: Torpedo shape and three angle vials. Dimensions: 6 1/2"L x 1 3/8" H x 5/8" W	\$580.00
L50M	MX Laser Micro Level™. (20 times brighter than standard model)	\$285.00
L25	Laser Handy Line with 650nm standard laser and 45 arc min. level vial.	\$195.00
L56-PT MSHA	Intrinsically Safe Red Laser Pointer. Includes Pen Clip and 2 AAA Alkaline Batteries. 7" x 3/4" Dia.	\$230.00
GL56-PT MSHA	Intrinsically Safe Green Laser Pointer. Includes Pen Clip and 2 AAA Alkaline Batteries. 7" x 3/4" Dia.	\$347.00
L56	Concentric Alignment Laser. Solid brass and waterproof. Includes a backlit 5 arc min.	\$595.00

level vial and a machined flat "V" groove. 635nm Bright Beam concentric to O.D.  
 2-"AAA" Batteries Included. Dimension: 6.5"L x 3/4" Dia.

L56 MSHA MSHA Certified L56 Concentric laser. \$980.00

<b>MODEL</b>	<b>DESCRIPTION</b>	<b>INDUSTRIAL</b>
L56S	Concentric Alignment Laser. Stainless Steel and waterproof. Includes a backlit 5 arc min. level vial and machined flat on bottom of case. 635nm Bright Beam concentric to O.D. 2-"AAA" Batteries Included. Dimension: 6.5"L x 3/4" Dia.	\$695.00
L56SS	Stainless Steel Bar Feeder Alignment Kit Includes L56SS Laser with 5 minute of arc level vial, 1/16" aperture, 1 - DT56C Clear target with grids, 1- DT56W White target with grids, DT56S Threaded 3/4" Adapter Sleeve, AP56 Magnetic Spindle Adapter and AP47 Hard Shell Carrying Case	\$995.00
GL56	Green Beam Technology™ Concentric Alignment Laser. Solid brass and waterproof. Includes a backlit 5 arc minute level vial and a machined flat "V" groove. 635nm Bright Beam concentric to O.D. 2-"AAA" Batteries Included. Dimension: 6.5"L x 3/4" Dia.	\$730.00
GL56 MSHA	Green Beam Technology™ MSHA Certified L56 Concentric laser.	\$1,390.00
L58AC	Alignment Module. Power:110 Volts AC. Includes 5' Cord and AC Adapter. Dimensions 3 1/4" L x .75" Dia.	\$399.00
L58DC	Alignment Module. Power: 4-24 Volts DC. Includes 5' Cord. Dimensions 3 1/4" L x .75" Dia.	\$350.00
L58SAC	Ecomony Alignment Module. Power 110 Vac, Includes 5' cord & AC Adapter	\$295.00
L58DRL	Center Point, Alignment Laser. Power 3 Volts DC. Includes Center Point and Beam. Dimensions 5 1/4" L x .75" Dia.	\$295.00
L58GM	Alignment Module. Power: 4.75-36 Volts DC. Includes 4 pin male Turck Power Connector. Dimensions 4 1/4" L x .75" Dia.	\$440.00
GLX58SAC-LINE	30mW, 515nm Green Laser Technology™ Laser Module with the CL002 70° Line Generator Lens. Includes: 110VAC Power Adapter and AP94A Mounting Bracket	\$395.00
GLX58BAC-SYS30	Beam Spreader™ System using 30mW Green Laser Technology™ Includes: GLX58BAC Green Laser Module, AP185A Beam Spreader™ with 60° Line Generator and AP185B Beam Shifter™ Adapter Plate. Input Power 110VAC, Class IIIa <5mW @515nm. Solid Brass Case.	\$795.00
GLX58BDC-SYS30	Beam Spreader™ System using 30mW Green Laser Technology™ Includes: GLX58SDC Green Laser Module, AP185A Beam Spreader™ with 60° Line Generator and AP185B Beam Shifter™ Adapter Plate. Input Power 12-36VDC, Class IIIa <5mW @ 515nm. Solid Brass Case.	\$795.00
GLX58BAC-30	Beam Spreader™ System using 30mW Green Laser Technology™ Includes: GLX58BAC Green Laser Module, AP185A Beam Spreader™ with 60° Line Generator and AP94 Mounting Bracket. Input Power 110VAC, Class IIIa <5mW @515nm. Solid Brass Case.	\$595.00
GLX58BDC-30	Beam Spreader™ System using 30mW Green Laser Technology™ Includes: GLX58BDC Green Laser Module, AP185A Beam Spreader™ with 60° Line Generator and AP94 Mounting Bracket. Input Power 12-36VDC, Class IIIa <5mW @ 515nm. Solid Brass Case.	\$595.00

L59AC	Alignment Module 1" O.D. Power 110 Volts AC. Includes 12.5 mm optics and 5' power cord. Laser Beam concentric to O.D. Dimensions 4"L x 1" Dia., Solid Brass	\$535.00
L59DC	Alignment Module 1" O.D. Includes 12.5 mm optics and 15' power cord. Operates from 4-24 VDC power. Laser Beam concentric to O.D. Dimensions 4"L x 1" Dia., Solid Brass	\$440.00
GL58AC	Green Laser Technology™ Alignment Module. Power:110 Volts AC. Includes 5' Cord and AC Adapter. Dimensions 3 1/4" L x .75" Dia.	\$720.00
<b>MODEL</b>	<b>DESCRIPTION</b>	<b>INDUSTRIAL</b>
GL58DC	Green Laser Technology™ Alignment Module. Power: 3 Volts DC. Includes 5' Cord. Dimensions 3 1/4" L x .75" Dia. (Order PS18 or PS36 for other power options)	\$645.00
GL59AC	Green Laser Technology™ Alignment Module 1" O.D. Power 110 Volts AC. Includes 12.5 mm optics and 5' power cord. Laser Beam concentric to O.D. Dimensions 4"L x 1" Dia., Solid Brass	\$847.00
GL59DC	Green Laser Technology™ Alignment Module 1" O.D. Includes 12.5 mm optics and 15' power cord. Operates on 3 VDC power. Laser Beam concentric to O.D. Dimensions 4"L x 1" Dia., Solid Brass (Order PS18 or PS36 for other power options)	\$752.00
L600AC	Laser Crosshair Generator. Power 110 VAC. Includes push button, on/off switch, 5' cord and AC adapter. Dimension: 4"L x 1 3/8"H x 3/4"W . AP94 Bracket	\$550.00
L600DC	Laser Crosshair Generator. Requires 4-24 Volts DC Power. Dimensions 4"L x 1 3/8"H x 3/4"W AP94 Bracket	\$490.00
GL600AC	Green Laser Technology™ Laser Crosshair Generator. Power 110 VAC. Includes push button, on/off switch, 5' cord and AC adapter. Dimension: 4"L x 1 3/8"H x 3/4"W	\$855.00
GL600DC	Green Laser Technology™ Laser Crosshair Generator. Power 3 VDC. Includes push button, on/off switch and 5' cord. Dimension: 4"L x 1 3/8"H x 3/4"W (Order PS18 or PS36 for other power options) (Order PS18 or PS36 for other power options)	\$820.00
GLX600AC-30	30mW, Green Laser Crosshair Generator. Includes 2- AP185A Beam Spreaders™, 2- AP185B Beam Shaper™ Adapter Plates with 60° Line Generators and AP94 Mounting Bracket. Hard Anodized Dual Laser Case with internal Power Regulator. Input Power 110VAC, Class IIIa <5mW @ 515nm. Includes Push On/Off Switch	\$995.00
GLX600DC-30	30mW, Green Laser Crosshair Generator. Includes 2- AP185A Beam Spreaders™, 2- AP185B Beam Shaper™ Adapter Plates with 60° Line Generators and AP94 Mounting Bracket. Hard Anodized Dual Laser Case with internal Power Regulator. Input Power 12-36VDC, Class IIIa <5mW @ 515nm. Includes Push On/Off Switch	\$995.00
L600DC GM	Laser Line Generator, requires 24 volts DC power. Dimension 4"L x 3/4"W x 3/8"H. (2 laser diodes,2 lines andTurck power connector)	\$680.00
L600DC P&G	Laser Line Generator, requires 24 volts DC power. Dimension 4"L x 3/4"W x 3/8"H. (1 laser diode,1 line and turck connector)	\$630.00
L750	Sea Beam™ Dual Beam, Underwater Red Laser System. 75mm spacing VideoRay 9 pin male plug	\$1,995.00
SB10	Sea Beam™ Dual Beam and Dual Power Red Laser Scaler. External power cord provided with internal battery option. Includes 60° Line Generator Lens.	\$2,350.00

SB20	Sea Beam™ Dual Beam Laser Scaler with external power cable provided to customer specification. Includes 60° Line Generator Lens.	\$1,995.00
GLXSB20	Sea Beam™ Dual Green Beam Laser Scaler with external power cable provided to customer specification. Includes 10 times bright laser beams, aluminum housing and 60° Line Generator Lens. Operates from 12VDC to 36VDC.	\$2,500.00
WL58	Waterproof Laser Module with red laser, 635nm Class IIIa, 5mW. External power cable provided to customer specifications. Includes 60° Line Generator Lens. Power 4.75VDC-36VDC	\$995.00

<b>MODEL</b>	<b>DESCRIPTION</b>	<b>INDUSTRIAL</b>
GWL58	Waterproof Laser Module with GLX Green Laser Diode, 515nm Class IIIa, 30mW. External power cable provided to customer specifications. Includes 60° Line Generator Lens. Power 12VDC-36VDC	\$1,250.00
WL56	Waterproof Laser Module with red laser. Battery operated with 2 AAA Alkaline Batteries for a 10-12Hr. continuous operation. Maximum depth is 1,000ft. (300m). Includes 60° Line Generator Lens.	\$995.00
GWL56	Waterproof Laser Module with Green Laser module. Battery operated with 2 AAA Alkaline Batteries for a continuous operation of 4-5 Hrs. Maximum depth is 1,000 ft. (300m). Includes 60° Line Generator Lens.	\$1,250.00
L80	Sheave Alignment System. Includes L80 Pulley Alignment Laser, 3- L80MT Magnetic Targets and Hard Shell Carrying Case.	\$995.00
L80 MSHA	MSHA Certified L80 Sheave Alignment System.	\$1,395.00
GL80	Green Laser Technology™ Sheave Alignment System. Includes L80 Pulley Alignment Laser, 3- L80MT Magnetic Targets and Hard Shell Carrying Case.	\$1,280.00
GL80 MSHA	Green Laser Technology™ MSHA Certified L80 Sheave Alignment System.	\$1,780.00
GL80 Trainer	Dayglow Sheave Alignment Trainer and Demonstrator. Includes sheaves, belt and adjustment screws.	\$564.00
HB59	Steel Enclosure for Outdoor Installations. Includes 110VAC Receptacle. 6"W x 6"H x 4"D	\$95.00
AP5	Modular Cord for connecting DT2 Sensor Unit to DT1 Display Unit. 5 ft. length	\$50.00
AP11	Stainless Steel Rock Bolt 3/4" - 10 x 11" Long	\$35.00
AP12	Stainless Steel Extension Nuts, Hex Sided 3/4" -10 x 1 3/4" Long	\$20.00
AP13	Rock Anchors 1 3/4" Diameter 3/4" - 10 x 5" Long	\$10.50
AP14	Modular Cord for connecting DT2 Sensor Unit to DT1 Display Unit. 14 Foot Length.	\$65.00
AP15	Aperture Pack. Includes 1/16", 3/32" & 1/8" Dia. apertures. (Fits L25, L50, L56 & L58)	\$55.00
AP16	Aperture Pack. Includes 1/16", 3/32", 1/8" & 13/64" Dia. apertures. (Fits L100, L350 & L700)	\$55.00
AP56	Magnetic Spindle Adapter includes adjustment screws (Fits L56SS and L56B Lasers)	\$195.00
AP65	Stainless Steel Gimbal Support Bracket Use with AP97 Mounting Block	\$50.00
AP80MT	Adjustable Magnet Target (For Pulley Alignment Kits)	\$66.00

AP92	Mounting Collar. (Use with al Lasers for fasten accessories)	\$39.00
AP93	Tri-Beam Bender™ Use with AP94 Mounting Bracket, AP11 SS Rock Bolt and AP13 Rock Anchor	\$499.00
AP94	Adjustable Mounting Assembly. Includes "L" bracket and laser mounting block.	\$75.00
AP94A	Adjustable Mounting Assembly. Includes "L" bracket and laser mounting block for 1" lasers. Non-Anodized, Glass Bead Finish	\$55.00
AP94B	Adjustable Mounting Assembly for 1 5/6" Diameter Laser Tubes. Includes "L" bracket and AP97 laser mounting block with mounting hardware.	\$170.00
<b>MODEL</b>	<b>DESCRIPTION</b>	<b>INDUSTRIAL</b>
AP94C	Adjustable Mounting Assembly for 1" Diameter Laser Tubes. Includes "L" bracket and laser mounting block with mounting hardware.	\$60.00
AP96	Hard Mount which includes: AP97 Mounting Block, 4- AP11 SS Rock Bolts, 2- AP12 Extension Nuts, 4- AP13 Rock Anchors 1 1/4" Dia., 2- AP94 Mounting Brackets, AP65 SS Gimbal Support Bracket, AP93 Tri-Beam Bender™ and AP46 Foam Filled, Hard Case Hard Case.	\$1,090.00
AP97	Mounting Block includes 1/4-20 hardware. Fits 1 5/8" Diameter GL350 Mining Laser	\$150.00
AP97A	Mounting Collar Adapter with 1" I.D. and 1 5/8" O.D. Fits into AP97 for mounting L350 Mining Laser	\$30.00
AP98	Magnetic support bracket system. Includes AP94 "L" bracket mounting assembly.	\$115.00
AP99	Magnetic Mounting Assembly. Includes: AP 94A Right Angle Support Bracket, AP354 Universal Magnetic Mounting Base and AP353A Magnetic Dovetail Mounting Base Plate	\$150.00
AP90C	Dual Vial 90° Beam Bender™ (Use w/ L100 Laser Precision Level)	\$155.00
AP180C	Dual Vial Beam Spreader™ (Use w/ L100 Laser Precision Level)	\$155.00
AP185A	Beam Shaper™ Even intensity Line Generator using Powell Lens Tech. Use with GLX Green Lasers.	\$150.00
AP185B	Intensity Shift Adapter Plate. Use with AP185 and AP185A Beam Shaper™ Line Gen. Lens Systems	\$205.00
AP100A	Leveling Adapter Plate. (For use will all lasers. Fits 5/8" x 11 Threaded Tripod.)	\$110.00
AP1000	Transit Adapter Plate w/ horizontal & vertical adjustment. (Fits 5/8" x 11 tpi tripods.)	\$475.00
AP1400	Rail and Gantry Alignment Kit. Includes: L202 Dual Beam Alignment Laser, AP90C Beam Bender™, LDM 150 LaserTape™, DT200 Retro-Reflective Magnetic Target and AP46 Hard Shell Carrying Case	\$1,299.00
AP1500	Mounting System. Includes: AP1000 leveling adapter plate, AP353 Dovetail Guide, Mounting Base Plate, and AP351 1" ring set (2). Mounts onto 5/8"-11tpi tripod. Dimensions 6.5"H x 5"L x 4" Dia.	\$760.00
AP1550	Rail Alignment Kit for 2,000 ft. Alignments. Includes: L355X Extremem Long Distance Alignment Laser, AP353A 5" Magnetic Mounting Base, 1" Ring Set, AP1000 Leveling Adapter Plate, DT200 Retro-Reflective Magnetic Target, LDM 150 Lasertape™ and AP46 Hard Shell Carrying Case.	\$2,260.00

AP1600	Tripod Mounting System Includes: AP1000 Leveling Adapter Plate, AP353 Mounting Base and AP97 Mounting Block for GL350 lasers. Order AP97A for L350 Laser	\$675.00
AP202	Support Bracket w/magnets. (Use with L202 and L600)	\$105.00
AP351	1" Ring Set (2) (Use w/ AP1500 mounting system)	\$95.00
AP353	Magnetic Dovetail Guide and Mounting Base Plate. 1" Long (Use with AP94)	\$75.00
AP353A	Magnetic Dovetail Guide and Mounting Base Plate. 5" Long (Use with L350 & L700)	\$145.00
AP354	Dovetail Mounting with magnetic base with holes for mounting AP90C & AP180C.	\$85.00
AP355	Beam Extender. Shoots beam 2 miles. (Use w/L350, L700, L100 & GLX LDs) * (Reqs. Circulaser diode w/	\$367.00
<b>MODEL</b>	<b>DESCRIPTION</b>	<b>INDUSTRIAL</b>
AP356	Beam Extender. Shoots beam 2 miles. (Use with GL350)	\$399.00
AP30	Soft Shell, plush lined and padded, 12" carrying case.	\$45.00
AP40	Hard Shell, foam filled case. Dimensions: 14"L x 10"W x 4"H. (Fits L100M)	\$55.00
AP41	Hard Shell, foam filled case. Dimensions: 17"L x 8" W x 9"H. (Fits L350)	\$55.00
AP42	Soft shell 18" plush lined and padded carrying case. (Fits L350)	\$45.00
AP43	Sheave Alignment System Hard Shell Carrying Case. Dimensions: 10 ½"L x 7"W x 3"H	\$55.00
AP44	PVC Hard Case with Screw Cap. 2" I.D., Foam Filled End Caps (Fits L350)	\$60.00
AP45	Soft Shell 21" Plush Lined and Padded Case (Fits L700)	\$47.00
AP46	Extra Large, foam filled hard case. Dimensions: 24"L x 10" H x 12" W (Fits L355, L700 & AP1500)	\$82.00
AP47	Sheave Alignment System Hard Shell Carrying Case. Dimensions: 10 ½"L x 7"W x 3"H Includes 4 built in case magnets for securing case to metal surfaces.	\$55.00
BE4.5V or BE6V	110 VAC Battery Eliminator replaces batteries in L50,L56 & L100 Lasers.	\$57.00
BP4.5V	4.5 VDC Battery Pack with switch. Uses 3 size AA batteries. (Use with L58, L59, L600 Lasers).	\$57.00
BP12V	12 VDC Battery Pack with Switch. Uses 8 Size AA Batteries. (Use with GLX Laser Systems)	\$57.00
IPA-220	International Power Adapter. Operates laser on 220 or 110 VAC @ 50 or 60 Hz. AC power plug not included.	\$135.00
PS18	DC to DC Power Adapter. 9-18 VDC input, 3.3 VDC output. 5' cord included Use with GL58DC and GL59 DC	\$135.00
GLD15	532nm Green Laser Diode System, 15 mW	\$285.00
WP58	Fine Beam Steering Optics. (Use with L56, L58, L202 & L600 style lasers.)	\$175.00
WP59	Fine Beam Steering Optics. (Use with L350, GL350, L100M L59 style lasers.)	\$399.00



WP600	Fine Line Adjustment. (Use with L56, L58, L202 & L600 style lasers.)	\$90.00
10LD	10MW, 635 nm laser Diode (20 times brighter beam)	\$175.00
CLD	* Blue Sky Research Circulaser with u lens: 635nm, 5mw	\$275.00
GLX-50	50mW Upgrade on all GLX Laser Systems per Laser Engine	\$100.00
CL1000	Built in Line Generator. 6° Divergent beam angle- 10' line @100'. (Use w/ L100M, L350 & AP180C).	\$97.00
CL2000	Built in Line Generator. 6° Divergent beam angle- 10' line @100'. (Use w/ L56, L202 & L50).	\$97.00
GL1000	Built in Line Generator. 6° Divergent beam angle- 10' line @100'. (Use w/ GL100M, GL350 & GL700).	\$97.00
GL2000	Built in Line Generator. 6° Divergent beam angle- 10' line @100'. (Use w/ GL56, GL202 & GL50).	\$97.00
<b>MODEL</b>	<b>DESCRIPTION</b>	<b>INDUSTRIAL</b>
CL40	Built in Line Generator. 40° Divergent beam angle- (Use w/ L350, L700 & L100).	\$97.00
CL50	Built in Line Generator. 35° Divergent beam angle- (Use w/ L202, L56, L58 & L600).	\$97.00
CL60	Built in Line Generator. 60° Divergent beam angle- (Use w/ L202, L56, L58 & L600).	\$97.00
CL2mm	70° Divergent Rod Lens 2mm Diameter (Use with GL80, GL58 and GL56)	\$110.00
CL150	1° Divergent Angle, 5/16" Line Length @ 18"	\$85.00
CL075	2° Divergent Angle, 5/8" Line Length @ 18"	\$85.00
CL025	3° Divergent Angle, 1" Line Length @ 18"	\$85.00
CL015	10° Divergent Angle, 3" Line Length @ 18"	\$85.00
CL007	20° Divergent Angle, 6" Line Length @ 18"	\$85.00
CL002	70° Divergent Angle, 25" Line Length @ 18"	\$85.00
CL360	300° Divergent Line Generator Lens Use with L56, L58, L202 and L600 both red and green lasers	\$285.00
POL 56	Adjustable Polarizer with Beam Correction Wedge Prisms. Dims laser light 50% to 1%. Fits L58 and L56 Thread types. Works with Red and Green Laser systems	\$150.00
POL A	Polarizing Lens in Lens can. 9/16-32 tpi thread. Fits L58 and L56 Thread Types	\$125.00
LV56	5 Min. of arc level vial. "Glow in the dark".	\$65.00
DT 56C	Clear Bar Feeder Target with Etched Grid	\$150.00
DT 56W	White Bar Feeder Target with Etched Grid	\$150.00
DT 56S	3/4" Threaded Adapter Sleeve	\$75.00

DT180	Red Translucent Magnetic Target. Dimensions: 3" x 4"	\$45.00
DT200	Red Retro-Reflective/Magnetic Target. Dimensions: 3" x 4"	\$59.00
AP354S-TAB	Stainless Steel adjustable tab with slot for hanging string. (Use with L350 & L700)	\$36.00
L350 BRACKET	Brass support bracket for tabs including mounting and adjustment screws. (Use with L350)	\$56.00
GL350 BRACKET	Brass support bracket for tabs including mounting and adjustment screws. (Use with GL350)	\$62.00
THUMB SCREWS	1 Pair stainless steel thumb screws. Replaces adjustment set screws used with brass support brackets.	\$46.00
L350 Bat. End Cap	Brass End Cap Switch for L350 Laser. Includes O ring and felt washer	\$57.00
GL350 Bat. End Cap	Brass End Cap Switch for GL350 Laser. Includes O ring and felt washer	\$90.00

<b>MODEL</b>	<b>DESCRIPTION</b>	<b>INDUSTRIAL</b>
--------------	--------------------	-------------------

Boss Joe	1 case of "Just In Case", All Natural, Bar-B-Q Sauce. 12 - 16 Oz. Bottles	\$50.00
Shipping Material	Cartonage, packing material and handling	\$10.00

OTHER \_\_\_\_\_

Credit Card No.	_____	<b>SUB TOTAL:</b>	_____
Exp. Date	_____ <b>CCV#</b> _____	<b>SHIPPING:</b>	_____
Name on Card	_____		
	UPS-RED _____ UPS GROUND _____ UPS Collect _____		
	Use Customer's Shipping Account # _____		

TOTAL: \_\_\_\_\_

Manufactured By: Laser Tools Co., Inc., 12101 Arch St., Little Rock, AR 72206  
 Web www.lasertoolsco.com, Phone 501-562-0900, 501-562-0022